1) **File: pageProperties.xml**

<u>Remove "Header Tabs" from the top of the Search Display.</u>

Comment out "Header Tabs" you do not want to display:

```
<!-- ## Remove MY LIST tab: LG 5/1/08
    <tab name="page.header.buttons.myList.button">
    <highlight
        pages="
            page.myList
        "/>
    </tab>
    -->
```

In this same file you can also edit the content of your search tips:

```
<page name="page.logIn" position="belowContent">
    <div class="instructionText"><span class="uiLabelRef">Mines</span> users
enter your 8-digit I.D. and Last Name, then click the <span class="uiLabelRef">Log
in</span> button (call 303-273-3022 for help).</div>
 <div class="instructionText"><span class="uiLabelRef">Guests</span> who want to
request an item should contact Interlibrary Loan at 303-273-3899.</div>
    </page>
```

This is straight HTML so you can format the text using tags like <UL> and etc.

(Note: The Title and Heading as well as the login TYPE are in webvoyage.properties)

In this file you can also customize the **no hits** message:

```
    </pageMsg>
    <pageMsg errorCode="searchResults.noHits">Search resulted in no hits. You may
want to check your spelling and try again.</pageMsg>
   </pageMessages>
```

You can make this text more user-friendly.

2) File: printCommon.xsl

<u>You can enter your institution's address info:</u>

```
<div id="printFooter">
        <div class="customContent">
                <label>Institution Name: Arthur Lakes
Library</label>
        </div>
        <div class="customContent">
                <label>Institution Address:1400 Illinois
Street, Golden Colorado, 80401</label>
        </div>
                <div class="customContent">
                        <label>Institution Web
Site:http://www.mines.edu/library</label>
                </div>
                <div class="customContent">
                        <label>Institution Phone:303-273-3911</label>
                </div>
```

CATALOG
A R T H U R L A K E S L I B R A R Y

Reinventing gravity : a physicist goes beyond Einstein /

Main Author: Moffat, John W.
Title: Reinventing gravity : a physicist goes beyond Einstein /
Format: Book
Publisher: New York : Smithsonian Books/Collins, c2008.

Holdings Information:

Location: Book Stacks (Floors 2, 2M & 3)
Call Number: QC178 .M64 2008
Number of Items: 1
Status: Available

Institution Name: Arthur Lakes Library
Institution Address:1400 Illinois Street, Golden Colorado, 80401
Institution Web Site:http://www.mines.edu/library
Institution Phone:303-273-3911

3) File: emailBody.xsl

Add your institution's address info:

```
Institution Name:  Arthur Lakes Library
Institution Address:  1400 Illinois Street, Golden CO 80401
Institution Web Site:  http://library.mines.edu
Institution Phone: 303-273-3022
Institution Email: libref@mines.edu
```

4) File: frameWork.xsl

<u>You can specify a favicon file:</u>

```
        <!-- ## Favicon ## -->
<link rel="shortcut icon" href="{$image-loc}favicon.ico" type="image/x-icon" />
<link rel="icon" href="{$image-loc}favicon.ico" type="image/x-icon " />
```

A favicon (short for favorites icon), also known as a shortcut icon, website icon, URL icon, or bookmark icon is a file containing one or more small icons, most commonly 16x16 pixels, associated with a particular website or webpage. It plays a role in branding.

5) File: tools.xsl

<u>Specify more helpful language for patrons when they encounter unknown blocks/errors/requests:</u>

```
<xsl:otherwise>
        <!-- This is a catch-all message for blocks/errors/requests -->
        The system could not process your request. Contact the Circulation
Desk with the following information: Define a page message block for <xsl:value-of
select="$blockCode"/> <xsl:value-of select="$errorCode"/> <xsl:value-of
select="$requestCode"/> in pageProperties.xml the server is returning a
block/error/request code and the client UI is not handling it.
        </xsl:otherwise>
```

Some status and other codes are undocumented, and a number will display in the OPAC rather than an explanation of the problem. These codes can be added, once you are informed they exist, to the webvoyage.properties file.

6) File: footer.xsl

<u>You can add additional footer "tabs" (or links)</u>

```
<xsl:template name="buildFooter">

   <xsl:for-each select="/page:page/page:pageFooter">
      <div id="pageFooter">
         <xsl:for-each select="page:tabs[@nameId='page.footer.buttons']">

            <div id="footerTabs" title="{$footerText/footerTabs}">
               <a name="navFooter"></a>
               <h2 class="navFooter"><xsl:value-of
select="$footerText/footerTabs"/></h2>
               <ul class="navbar">
                  <xsl:for-each
select="$Configs/pageConfigs/footerTabDisplayOrder/tab">
                     <xsl:variable name="tempName" select="@name"/>
                     <xsl:variable name="newWin" select="@clickOpensNewWindow"/>
                     <xsl:call-template name="buildFooterTab">
                        <xsl:with-param name="displayTab" select="$tempName"/>
                        <xsl:with-param name="newWin" select="$newWin"/>
                        <xsl:with-param name="highlight" select="highlight/@pages"/>
                     </xsl:call-template>
                  </xsl:for-each>
                  <!-- extra footer tabs -->
<li>
<a href="http://prospector.coalliance.org" title="Search Prospector">Search
Prospector</a>
</li>
<li>
<a href="http://goldrush.coalliance.org/index.cfm?fuseaction=Article%20Finder"
title="Find an Article Online">Find an Article Online</a>
</li>
<li>
<a href="http://goldrush.coalliance.org/index.cfm?inst_code=001_CSM" title="Look for
Electronic Journals">Look for Electronic Journals</a>
</li>
<li>
<a href="http://library.mines.edu" title="Exit Session">Exit</a>
</li>
<!-- end of extra footer tabs -->
               </ul>
            </div>

      </xsl:for-each>
```

7) File: header.xsl

Add "Exit" to the "Header Tabs":

```xml
<xsl:template name="buildHeader">
    <xsl:for-each select="/page:page/page:pageHeader">
        <div id="headerRow">
            <div id="logo" title="{$headerText/logo}">

                <xsl:call-template name="buildImageUrl">
                    <xsl:with-param name="eleName" select="'page.header.logo.image'"/>
                </xsl:call-template>

            </div>
            <div id="patronCol">
                <xsl:call-template name="loginLogout"/>
                <div id="headerHelp" title="{$headerText/help}">
                    <span>
                        <a href="{page:element[@nameId='page.header.help.link']/page:URL}"
target="help">
                            <xsl:value-of
select="page:element[@nameId='page.header.help.link']/page:linkText"/>
                        </a> <xsl:value-of
select="page:element[@nameId='page.header.help.link']/page:postText"/>
                    </span>
                </div>
            </div>
            <xsl:for-each select="page:tabs[@nameId='page.header.buttons']">
                <div id="headerTabs" title="{$headerText/headerTabs}">
                    <a name="mainNav"></a>
                    <h2 class="nav"><xsl:value-of select="$headerText/headerTabs"/></h2>
                    <ul class="navbar">
                        <xsl:for-each
select="$Configs/pageConfigs/headerTabDisplayOrder/tab">
                            <xsl:variable name="tempName" select="@name"/>
                            <xsl:call-template name="buildHeaderTab">
                                <xsl:with-param name="displayTab" select="$tempName"/>
                                <xsl:with-param name="highlight" select="highlight/@pages"/>
                            </xsl:call-template>
                        </xsl:for-each>

        <!-- This modification adds an exit button to the header tabs 2008/05/05 -->
                        <li class="off" title="Exit Session">
                            <a href="exit.do" name="Exit Button">
                                <span>Exit</span>
                            </a>
                        </li>
                        <!-- End modification to add an exit button -->
                    </ul>
                </div>
            </xsl:for-each>
        </div>
    </xsl:for-each>
</xsl:template>
```

8) File: searchFacets.xsl

<u>Disable autocomplete of search box:</u>

```
<div id="searchForm">
      <form action="{$formAction}" method="GET" accept-charset="UTF-8"
id="{$formName}" autocomplete="off">
          <xsl:copy-of select="$formData"/>
      </form>
```

9) File: displaycfg.xml

<u>Do you have Syndetics? If so you can add your book covers here:</u>

```
    <coverTags altText="Book Cover Image" title="Click for Table of Contents,
Reviews, Summary, etc." linkPRE_TEXT="http://www.syndetics.com/hw7.pl?isbn="
linkPOST_TEXT="/MC.jpg&amp;showCaptionBelow=t&amp;caption=Click here for
more&amp;&amp;client=yourcodehere"
infoPRE_TEXT="http://syndetics.com/index.aspx?isbn="
infoPOST_TEXT="/index.html&amp;client=yourcodehere&amp;type=rn12"
singleInstance="true">
        <displayTag field="020" indicator1="X" indicator2="X" subfield="a"/>
    </coverTags>
```


<u>Don't have Syndetics? Here's an Open Library tag that might (or might not!) work:</u>

```
<coverTags altText="Book Cover" linkPRE_TEXT="http://covers.openlibrary.org/b/isbn/"
linkPOST_TEXT="-M.jpg" class="recordCoverImage" singleInstance="true">
        <displayTag field="020" indicator1="X" indicator2="X" subfield="a"/>
    </coverTags>
```

10) File: displayHoldings.xml

<u>Call Number redirect code:</u>

```
        <holdingsTags label="Call Number:" notFound="No call number available">
            <displayTag field="852" indicator1="X"  indicator2="X" subfield="khij"
redirect="callnumber" redirectOn="hi"/>
        </holdingsTags>
```

Locate this Item

Location:	Book Stacks (Floors 2, 2M & 3)
Call Number:	QC178 .M64 2008
Number of Items:	1
Status:	Available

<u>Comment out 1002 (Database:) in holdings:</u>

```
<!--
        <holdingsTags label="Database:" notFound="No information available">
            <displayTag field="1002" />
        </holdingsTags>
-->
```

Holdings Information

Database:	Arthur Lakes Library
Location:	Book Stacks (Floors 2, 2M & 3)
Call Number:	QC178 .M64 2008
Number of Items:	1
Status:	Not Charged
Back to library list	

11) File: limits.xml

<u>This is one place you can control what categories display and which fields appear in each category:</u>

```
<!-- Remove Status Drop-down
    <limitGroup type="status" label="Status:">
            <limit code="all" default="Y">All Status</limit>
            <limit code="c">Currently Published</limit>
            <limit code="d">Ceased Publication</limit>
            <limit code="u">Unknown</limit>
      </limitGroup>
-->
```

12) File: …/vwebv/context/vwebv/htdocs/index.html

<u>Bypass the default start page by changing the entire contents of this file to go directly to your default search:</u>

```
<script language="javascript">
window.location.href="http://xxx.xxxxxx.edu/vwebv/searchBasic?sk=en_US
" </script>
```

13) File: …/vwebv/context/vwebv/error_500.html

Change error redirect to link of your choice:

```
<head>

 <META http-equiv="Content-Type" content="text/html; charset=UTF-8">

 <!-- CHANGEME: verify the URL in the next line is where this page should redirect -->

 <META http-equiv="Refresh" content="10;URL=http://xxx.xxxxx.edu"/>

 <style type="text/css">@import "/vwebv/ui/en_US/css/frameWork.css";</style>

 <style type="text/css">@import "/vwebv/ui/en_US/css/header.css";</style>

 <style media="screen" type="text/css">@import
"/vwebv/ui/en_US/css/quickSearchBar.css";</style>

 <link href="/vwebv/ui/en_US/css/help.css" rel="stylesheet" type="text/css">

 <title>Catalog System Error</title>

</head>
```

14) File: webvoyage.properties

There are many things you can change in this file!

Your welcome message (sometimes called "Database Name"):

```
connect.db.LOCAL.name=The Catalog contains information about print and electronic
books, print and electronic journals, government documents, maps and other materials
at the Arthur Lakes Library, Colorado School of Mines.
```

Basic Search

Welcome: The Catalog contains information about print and electronic books, print and electronic journals, government documents, maps and other materials at the Arthur Lakes Library, Colorado School of Mines.

Exit Page (the "exit.do" command is used in several different places):

```
#==============================================================================#
# What page or URL should the system go to in response to the exit.do action?
# This can be a WebVoyage page, such as searchBasic, or an external URL
#==============================================================================#
option.exitURL=http://library.mines.edu
```

Footer section:

```
page.footer.library.linktext=Your Library Name Here

page.footer.library.link=http://your.librarylink.here
```

(or change this to some other link!)

| Search | My Searches | My List | My Account | Help | Search Prospector | Find an Article Online | Look for Electronic Journals | Exit |

Ask a Librarian

©2011 Ex Libris G... All rights reserved.

Search the Catalog from your mobile device

Customize your basic search types and labels:

```
page.search.basic.search.code.leftAnchorTitle=
page.search.basic.search.code.leftAnchorTitle.code=TALL
page.search.basic.search.code.leftAnchorTitle.order=6
page.search.basic.search.code.leftAnchorTitle.display=Title Begins With (omit leading
articles)
```

Note: if you use the TALL index in Classic and are switching to Tomcat, you'll have to add Title to the Selected Bib Text area in SYSADMIN Search Results tab for the title to appear in the results list:

Modify the Search Index Definitions used in the Advanced search page

```
# Search Index Definitions
# ========================
# Search Index definitions are used on the Advanced search page. This section
# allows the name of the index to be changed from what is defined in SysAdmin.
# The order of these entries is controlled by the database.
```

<u>Modify the Basic Search Quick Limits in the Limit To stanza:</u>

You can limit by:

- Location Limit Groups
- Item Type
- Item Status
- Publication Date
- Place
- Language
- Dual-criteria limits are now available!

```
page.search.limitTo.selected=none
page.search.limitTo.none=
page.search.limitTo.none.limit=none
page.search.limitTo.none.order=1
page.search.limitTo.none.text=All Material
page.search.limitTo.Archive=
page.search.limitTo.Archive.limit=LOCA=Archive
page.search.limitTo.Archive.order=2
page.search.limitTo.Archive.text=Archive
page.search.limitTo.Stacks=
page.search.limitTo.Stacks.limit=LOCA=Book Stacks
page.search.limitTo.Stacks.order=3
page.search.limitTo.Stacks.text=Book Stacks
```

Enable Email:

```
option.email=Y
mail.host=
mail.transport.protocol=smtp
mail.user=voyager
mail.subject=Search Results
```

plus:

```
page.searchResults.browseBar.email.button=E-mail
page.searchResults.browseBar.email.button.message=E-mail the search results
```

and don't forget:

```
actionBox.actions.email.linkText=E-mail
```

Disable the Holdings Jump Bar:

```
db.holdings.jumpBar=N
```

Customize browser headings, search type titles, hover text and etc:

```
page.search.author.title=Author Search
page.search.author.heading=Author Search
page.search.authorPage.label=Author Search
page.search.author.label=Author:
page.search.author.message=Enter an author's name to search the Author Index
page.search.author.lastName.argument.label=Last Name
page.search.author.firstName.argument.label=Initials or First Name
```

Get rid of "More about this Item" SFX Link in the Action Box

In webvoyage.Properties comment out

`actionBox.moreAboutThisItem=More About This Item`

and

In the holdingsInfo.vbib.properties file change the switch to N in

`actionBox.openUrl.cfg.LOCAL.openUrlDisplay=N`

This item
    Record View
      · Staff View

Actions
    · Make a Request
   (e.g. Hold, Recall, Photocopy)
    · Print
    · Export
    · Add to My List

More About This Item From
   S·F·X

15) Record display

The equivalent of displayX.cfg and displayh.cfg in WebVoyage Classic are:
…/skin/xsl/contentLayout/configs/**displaycfg.xml** and **displayHoldings.xml**

You can change the order of the fields and which fields display, as well as control redirects. Be very, very careful when you edit these files and always keep known good backups.

Change "Holdings Information" to "Locate this Item" in displaycfg.xml

```
    <displayTags label="Locate this Item" notFound="No holdings available -- check at
the Circulation Desk.">
        <displayTag field="9000"/>
    </displayTags>
```

Locate this Item

Location:	Book Stacks (Floors 2, 2M & 3)
Call Number:	QC178 .M64 2008
Number of Items:	1
Status:	Available