

CHAINS

CHAINS

Description of 1/4 Sec. cor. bet. Secs. 4 and 5 and the closing corners at NE. cor. of Sec. 5 Tp. 6 S. R. 78 W. 6 P.M.	
	North bet. Secs. 4 and 5 on a true line. 18.00
	Va. 14° 45' E. 31.25
2.00	Foot of rocky ledge. 32.25
8.00	Top of same. 40.00
15.00	Enter timber. 48.50
18.00	Foot of mountain. 50.00
26.00	D. and R. G. R. R. bears NE. and SW. cliffs
33.00	Ten Mile Creek 62 lks. water, course NE. E.
35.00	Road bears N. 70° E. and S. 70° W. 10.00
36.00	Foot of rocks on mountain side. 10.00
40.00	Top of cliff. raised a mound of stone alongside
	Set a granite stone 18 x 8 x 3 ins. 12 ins. in the ground for 1/4 Sec. cor., marked 1/4 on W. face and raised a mound of stone alongside.
	No trees within 3 chs. East on a random line
82.38	Intersect 1st Correction Line S. at a point 8.92 chs. E. of the Standard 1/4 cor. to Sec. 33, Tp. 5 S. R. 78 W., at which point I set a sandstone 20 x 15 x 10 ins. 15 ins. in the ground for closing cor. to Secs. 4 and 5, Tp. 6 S. R. 78 W., marked C. C., with 4 notches on E. and 2 notches on W. edges and raised a mound of stone alongside. 10.00
	No trees within 3 chs. cliffs
	Surface mountainous. thence I run back W. on
	Soil sandy, 3rd rate. Va. 14° 45' E.
	Scattered pine and spruce. Set a granite stone 10.00
	Buffalo grass. Ground for 1/4 Sec. cor., marked 1/4 on W. face and raised a mound of stone alongside.
	Oct. 3rd, 1882.
	No trees within 3 chs.

CHAINS

<u>Description of 1/4 Sec. cor. bet. Secs. 8 and 17.</u>	
	East on a random line bet. Secs. 8 and 17. Va. 14° 45' E.
18.00	Foot of mountain.
31.25	D. and R. G. R. R. bears N. and S.
36.10	Road bears N. and S.
40.00	Set temp. 1/4 Sec. cor. in bottom.
48.50	Ten Mile 50 lks. water, course N. 3° E.
50.00	Foot of very rocky mountain with high perpendicular cliffs, finding it impossible to run the line farther E. I here abandon line and run back W. on same line.
10.00	Set a granite stone 12 x 12 x 3 ins., 8 ins. in the ground for 1/4 Sec. cor., marked 1/4 on N. face and raised a mound of stone alongside.
	No trees within 3 chs.

<u>Description of 1/4 Sec. cor. bet. Secs. 5 and 8.</u>	
	East on a random line bet. Secs. 5 and 8. Va. 14° 45' E.
16.00	Leave timber at foot of mountain.
31.25	D. and R. G. R. R. bears N. 60° E. and S. 60° W.
34.50	Ten Mile 63 lks. water, course NE.
38.00	Road, bears NE. and SW.
40.00	Set temp. 1/4 Sec. cor. at foot of rocky ledge.
76.00	Gulch, 1 lk. water, course NW. at foot of high rocky cliffs, finding it impossible to proceed farther E. thence I run back W. on same line. Va. 14° 45' E.
36.00	Set a granite stone 16 x 6 x 4 ins., 11 ins. in the ground for 1/4 Sec. cor., marked 1/4 on N. face and raised a mound of stone alongside.
	No trees within 3 chs.

CHAINS

BLIND

Description of SW. corner of Sec. 34, Tp. 5 S. R. 78 W.

Set granite stone 20 x 8 x 6 ins., 4 ins. in ground to bed rock, with a mound of stones for cor. to Secs. 33 and 34, marked S C, with 3 notches on E. and W. sides, from which  
 A dead pine 14 ins. dia. bears N. 8° W. 13 lks. dist. marked T 5 S R 78 W S 33 B T  
 A mark X cut on face of rock in place, a ledge of indeffinite extent bears West 28 lks. dist., marked B R cor. No. 6 of Mineral Survey No. 2193 bears N. 28° 55' E. 31.87 chs. dist.  
 Witness cor. post marked "W C 3 - 5606" bears N. 39° 8' E. 46.98 chs. dist.  
 Witness cor. post marked "W C 6 - 5610" bears N. 39° 23' E. 41.74 chs.

Description of 1/4 cor. bet. Secs. 33 and 34 and of SW. cor. of Sec. 27.

From the cor. to Secs. 33 and 34 on the S. Bdy. of the Tp., which is a granite stone 16 x 8 x 6 ins. above ground with a mound of stones marked S C, with 3 notches on E. and W. edges, from which  
 A dead pine 14 ins. dia. bears N. 8° W. 13 lks. dist. marked T 5 S R 78 W S 33 B T.  
 A mark X cut on rock in place bears West 28 lks. dist. marked B R.  
 I run  
 N. 0° 20' W. on line bet. Secs. 33 and 34.

Va. 14° 00' E.

8.60 Descending steep mountain side, with dead fallen timber. Denver and South Park Railroad, course N. 51° 49' E. Enter bottoms.

8.95 Right bank of Ten Mile Creek 60 lks. wide, course N. 52° E.

CHAINS

14.49 Denver and Rio Grande Railroad, course N. 55° 29' E.  
 15.20 Wagon road, course N. 56° E.  
 18.00 Foot of steep mountain spur.  
 31.45 Top of cliff 600 ft. above railroad, course N. 75° E.  
 38.00 Descend steep rocky slope.  
 40.00 Set a granite stone 20 x 17 x 7 ins. in a mound of

stones for 1/4 Sec. cor., marked 1/4 on W. face,  
 from which  
 An aspen 3 ins. dia. bears N. 70° E. 19 lks. dist.,  
 marked 1/4 S B T.  
 An aspen 3 ins. dia. bears S. 76° W. 30 lks. dist.,  
 marked 1/4 S B T.

53.66 Right bank of North Ten Mile Creek, 40 lks. water,  
 course N. 77° E., at foot of steep mountain in a  
 narrow gorge.  
 Ascend.

56.76 Wagon road from timber to Frisco, course N. 85° E.

56.93 Ditch, dry, 3 lks. wide, course N. 80° E.

80.00 Set a granite stone 20 x 9 x 5 ins., 15 ins. in the  
 ground with mound of stones for cor. to Secs. 27,  
 28, 33 and 34, marked with 1 notch on S. and 3  
 notches on E. sides, from which  
 A spruce 26 ins. dia. bears N. 83° E. 28 lks. dist.,  
 marked T 5 S R 78 W S 27 B T.  
 A dead pine 25 ins. dia. bears S. 33° 30' E. 30 lks.  
 dist., marked T 5 S R 78 W S 34 B T.  
 A spruce 32 ins. dia. bears S. 64° W. 64 lks. dist.,  
 marked T 5 S R 78 W S 33 B T.  
 No other trees near.

Description of cor. bet. Secs. 8 and 9.

N. 0° 21' W. bet. Secs. 8 and 9.  
 Va. 14° 30' E.

Descending NE. slope of mountain.

31.28 Right bank of North Willow Creek 20 lks. wide, course  
 N. 85° E.

1366  
 8196  
 8196  
 901.56  
 1/4 cor to creek

5693  
 5366  
 3.27  
 1966  
 1962  
 21582  
 creek to ditch

901.56  
 21582  
 1117.48  
 ditch to 1/4 cor.

2640  
 2064  
 576

## CHAINS

40.00

Set a granite stone 14 x 6 x 6 ins. 9 ins. in the ground for 1/4 Sec. cor., marked 1/4 on W. face, from which

A spruce 11 ins. dia. bears S. 79° E. 39 lks. dist., marked 1/4 S B T.

A spruce 22 ins. dia. bears S. 45 1/4° W. 14 lks. dist., marked 1/4 S B T.